










HCMOS  page O-1	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Tolerance	Pin #1 & Symmetry	Frequency
	5 x 7.5 x 1.6 Max. 0.197 x 0.29 x 0.07	HCMOS /TTL	5x7mm SMD	<u>1</u> = 5V <u>3</u> = 3.3V	<u>A</u> = 0E to 70EC <u>B</u> = -40E to 85EC	<u>0D</u> = ±100ppm <u>1D</u> = ±50ppm	<u>A</u> =Pin #1 Enable Hi <u>D</u> =45/55% Symmetry	(MHz)
	Part Number	CH	5	1	A	0D	AD	40M00000
HCMOS  page O-2	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Tolerance	Options	Frequency
	20.8 x 13.2 x 5.1 0.82 x 0.52 x 0.20	HCMOS /TTL	Full Size	<u>1</u> = 5V <u>3</u> = 3.3V	<u>A</u> = 0E to 70EC <u>B</u> = -40E to 85EC	<u>0D</u> = ±100ppm <u>1D</u> = ±50ppm	<u>A</u> =Pin #1 Enable Hi <u>D</u> =45/55% Symmetry	(MHz)
	Part Number	CH	1	1	A	0D	AD	40M00000
HCMOS  page O-2	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Tolerance	Options	Frequency
	20.8 x 13.2 x 5.1 0.82 x 0.52 x 0.20	HCMOS /TTL	Full Size GullWing	<u>1</u> = 5V <u>3</u> = 3.3V	<u>A</u> = 0E to 70EC <u>B</u> = -40E to 85EC	<u>0D</u> = ±100ppm <u>1D</u> = ±50ppm	<u>A</u> =Pin #1 Enable Hi <u>D</u> =45/55% Symmetry	(MHz)
	Part Number	CH	3	1	A	0D	AD	40M00000
HCMOS  page O-3	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Tolerance	Options	Frequency
	13.2 x 13.4 x 5.08 0.52 x 0.52 x 0.20	HCMOS /TTL	Half Size	<u>1</u> = 5V <u>3</u> = 3.3V	<u>A</u> = 0E to 70EC <u>B</u> = -40E to 85EC	<u>0D</u> = ±100ppm <u>1D</u> = ±50ppm	<u>A</u> =Pin #1 Enable Hi <u>D</u> =45/55% Symmetry	(MHz)
	Part Number	CH	2	1	A	0D	AD	40M00000
HCMOS  page O-3	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Tolerance	Options	Frequency
	13.2 x 13.4 x 5.08 0.52 x 0.52 x 0.20	HCMOS /TTL	Half Size GullWing	<u>1</u> = 5V <u>3</u> = 3.3V	<u>A</u> = 0E to 70EC <u>B</u> = -40E to 85EC	<u>0D</u> = ±100ppm <u>1D</u> = ±50ppm	<u>A</u> =Pin #1 Enable Hi <u>D</u> =45/55% Symmetry	(MHz)
	Part Number	CH	4	1	A	0D	AD	40M00000
TTL  page O-4	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Tolerance	Options	Frequency
	20.8 x 13.2 x 5.1 0.82 x 0.52 x 0.20	TTL	Full Size	<u>1</u> = 5V <u>3</u> = 3.3V	<u>A</u> = 0E to 70EC <u>B</u> = -40E to 85EC	<u>0D</u> = ±100ppm <u>1D</u> = ±50ppm	<u>A</u> =Pin #1 Enable Hi <u>D</u> =45/55% Symmetry	(MHz)
	Part Number	T	1	1	A	0D	AD	40M00000
TTL  page O-4	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Tolerance	Options	Frequency
	20.8 x 13.2 x 5.1 0.82 x 0.52 x 0.20	TTL	Full Size GullWing	<u>1</u> = 5V <u>3</u> = 3.3V	<u>A</u> = 0E to 70EC <u>B</u> = -40E to 85EC	<u>0D</u> = ±100ppm <u>1D</u> = ±50ppm	<u>A</u> =Pin #1 Enable Hi <u>D</u> =45/55% Symmetry	(MHz)
	Part Number	T	3	1	A	0D	AD	40M00000
TTL  page O-5	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Tolerance	Options	Frequency
	13.2 x 13.4 x 5.08 0.52 x 0.52 x 0.20	TTL	Half Size	<u>1</u> = 5V <u>3</u> = 3.3V	<u>A</u> = 0E to 70EC <u>B</u> = -40E to 85EC	<u>0D</u> = ±100ppm <u>1D</u> = ±50ppm	<u>A</u> =Pin #1 Enable Hi <u>D</u> =45/55% Symmetry	(MHz)
	Part Number	T	2	1	A	0D	AD	40M00000
TTL  page O-5	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Tolerance	Options	Frequency
	13.2 x 13.4 x 5.08 0.52 x 0.52 x 0.20	TTL	Half Size GullWing	<u>1</u> = 5V <u>3</u> = 3.3V	<u>A</u> = 0E to 70EC <u>B</u> = -40E to 85EC	<u>0D</u> = ±100ppm <u>1D</u> = ±50ppm	<u>A</u> =Pin #1 Enable Hi <u>D</u> =45/55% Symmetry	(MHz)
	Part Number	T	4	1	A	0D	AD	40M00000