

 page O-12	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Output Wave	Frequency	Freq. Stability
	15 x 25 x 14 0.59 x 0.98 x 0.55	DTCXO	Thru-Hole	5V	<b>A</b> = 0E to 70EC <b>B</b> = -20E to 70EC	<b>H</b> =CMOS & TTL <b>S</b> =Sine Wave	(MHz)	±1.0~±0.3ppm
	<b>Part Number</b>	<b>DTC</b>	<b>1525T</b>		<b>A</b>	<b>H</b>	<b>12M288000</b>	<b>-1.0</b>
 page O-13	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Output Wave	Frequency	Freq. Stability
	12.6 x 18.6 x 10 0.49 x 0.73 x 0.40	TCXO	Thru-Hole	5V	<b>A</b> = 0E to 60EC <b>B</b> = -20E to 70EC	<b>H</b> =CMOS & TTL <b>S</b> =Sine Wave	(MHz)	±10.0~±0.3ppm
	<b>Part Number</b>	<b>TC</b>	<b>1218T</b>		<b>A</b>	<b>H</b>	<b>12M288000</b>	<b>-10.0</b>
 page O-14	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Output Load	Frequency	Freq. Stability
	7.0 x 9.0 x 2.0 0.28 x 0.36 x 0.08	TCXO	7x9 SMD 4 pad	3V	-20E to 75EC	[10k Ohms/10pF]±10%	(MHz)	see Page O-14
	<b>Part Number</b>	<b>TC</b>	<b>79-4-</b>				<b>12M288000</b>	
 page O-15	Dimensions mm/inch	Family/ Package	Freq. Stability	Temp. Range	Output Load	Freq. Deviation	Frequency	
	7.62 x 18.3 x 4.5 0.3 x 0.72 x 0.18	TC & VCXO 14 Pin SMD 5Vdc	See Table Page O-15 (2 digit code)	See Table Page O-15 (1 letter code)	<b>C</b> = CMOS/ TTL Compatible <b>S</b> = Clipped Sinewave	<b>Blank</b> = TCXO <b>5</b> = ±5ppm <b>10</b> = ±10ppm	(Mhz)	
	<b>Part Number</b>	<b>TVCFS</b>	<b>25</b>	<b>C</b>	<b>S</b>	<b>10</b>	<b>12M28800</b>	
 page O-16	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Output Load	Frequency	Freq. Stability
	9.6 x 11.4 x 2.3 0.38 x 0.45 x 0.09	VTCXO	9x11 SMD 4 pad	3V	-30E to 75EC	10k Ohms/10pF	(MHz)	see Page O-16
	<b>Part Number</b>	<b>VTC</b>	<b>911-4-</b>				<b>12M288000</b>	
 page O-17	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Output Load	Frequency	Freq. Stability
	9.6 x 11.4 x 2.3 0.38 x 0.45 x 0.09	VTCXO	9x11 SMD 6 pad	3V	-30E to 75EC	10k Ohms/10pF	(MHz)	see Page O-17
	<b>Part Number</b>	<b>VTC</b>	<b>911-6-</b>				<b>12M288000</b>	
 page O-18	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Output Load	Frequency	Freq. Stability
	3.2 x 5.0 x 1.5 0.13 x 0.20 x 0.06	VTCXO	3x5 SMD 4 pad	3V	- 20E to 75EC	[10k Ohms/10pF]±10%	(MHz)	see Page O-18
	<b>Part Number</b>	<b>VTC</b>	<b>35-4-</b>				<b>12M288000</b>	
 page O-19	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Freq. Stability	Output Load	Frequency
	7.0 x 9.0 x 2.0 0.28 x 0.35 x 0.08	VTCXO	7x9 SMD 4 pad	3V	- 20E to 75EC	<b>2.5</b> = ±2.5ppm <b>5</b> = ±5ppm	[10k Ohms/10pF]±10%	(MHz)
	<b>Part Number</b>	<b>VTC</b>	<b>79-</b>			<b>5-</b>		<b>12M288000</b>
 page O-20	Dimensions mm/inch	Family	Package	Voltage	Temp. Range	Output Load	Frequency	Freq. Stability
	3.5 x 6.0 x 1.7 0.14 x 0.24 x 0.07	VTCXO	3x6 SMD 4 pad	3V	- 30E to 80EC	10pF/ 10k Ohms	(MHz)	±2.5ppm see Page O-20
	<b>Part Number</b>	<b>VTC</b>	<b>36-4-</b>				<b>12M288000</b>	